

specifications

- ▶ A color coded label on the Front plate shall be used for gas identification and aesthetic appeal.
- ▶ Satin finish Latch-Valve Assembly are available for Ohemda Compatible, DISS, Puritan Bennet Compatible, and Chemetron Compatible
- ▶ All Satin Finish Latch-Valve Assemblies shall be cleaned and degreased for medical gas service, factory assembled and tested.
- ▶ Flow rate exceeds the requirements of NFPA and CSA.
- ▶ Satin Finish Latch-Valve Assemblies are UL Listed and CSA approved.
- ▶ Amico products comply with NFPA-99



FRONT

The XX defines the latch-valve assembly style:

- QD = Ohmeda Compatible
- CH = Chemetron Compatible
- PB = Puritan-Bennett Compatible
- DI = DISS

O-FAOC-XX-L-XXX

The L defines the Language:

- U = English (NFPA)
Oxy, Air, Vac & WAG
- E = English (CSA/ISO)

model numbers

The XXX defines the Gas:

- Oxygen = OXY
- Medical Air = AIR
- Nitrous Oxide = N2O
- Carbon Dioxide = CO2
- MedVac = VAC
- Waste Anesthetic Gas Disposal (NFPA) = WAG
- Anesthetic Gas Scavenging System (CSA) = AGS

NOTE: Rough in and trim plate sold separately

project

represented by:

Amico Corporation
85 Fulton Way, Richmond Hill, ON L4B 2N4, Canada
31 Sprague Avenue, Amityville, NY 11701, USA

Toll Free Tel: 1.877.462.6426 | Toll Free Fax: 1.866.440.4986
Tel: 905.764.0800 | Fax: 905.764.0862
www.amico.com

Dec-08